

WPT1

LED Wall Pack Traditional



FEATURES:

- Robust die-cast aluminum housing
- High impact, heat resistant borosilicate glass lens
- Low-wattage consumption with highly efficient patented LEDs
- 120 -277V or 277-480V wide range input voltage
- Complies with UL1598 and CSA C22.2
- DLC Premium Qualified
- 100,000H @L70 long lifetime



ORDERING GUIDE Example: WPT1-40-730-UV10V-BZ

PART #	WATTAGE (W) & LUMEN & EFFICACY	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WPT1				
	40 : 40W 5600LM 135 lm/W	7 : 70 3000K	UV : 120~277V 10V: 0-10V Dimming Universal Voltage	BZ: Bronze
	60 : 60W 8100LM 135 lm/W	4000K		
		5000K	HV : 277V~480V High Voltage	

WPCA

LED Wall Pack Full Cutoff Adjustable



FEATURES:

- Robust die-cast aluminum housing
- Elegant yet rugged construction effortlessly integrates with existing architecture.
- Low-watt consumption with high-efficient LEDs
- 90 degree adjustable mounting angle
- 120 -277V or 277-480V wide range input voltage
- Complies with UL1598 and CSA C22.2
- DLC Premium Qualified
- 100,000H @L70 long lifetime



ORDERING GUIDE Example: WPCA-37-730-UV10V-BZ

PART #	WATTAGE (W) & LUMEN & EFFICACY	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WPCA				
	37 : 37W 4700LM 126 lm/W	7 : 70 3000K	UV : 120~277V 10V: 0-10V Dimming Universal Voltage	BZ: Bronze
	58 : 58W 7600LM 133 lm/W	4000K		
	70 : 70W 10200LM 140 lm/W	5000K	HV : 277V~480V High Voltage	



UiLED Technology Ltd.
www.uiled.cn

C2314 Innovation Plaza, Pingshan Avenue, Shenzhen, 518118 China
Tel: (86) 8999 4991 Email: info@uiled.cn / sales@uiled.cn



FEATURES:

- Robust die-cast aluminum housing
- High impact, heat resistant borosilicate glass lens
- Low-wattage consumption with highly efficient patented LEDs
- 120 -277V or 277-480V wide range input voltage
- Complies with UL1598 and CSA C22.2
- DLC Premium Qualified
- 100,000H @L70 long lifetime



ORDERING GUIDE Example: WPSL-40-730-UV10V-BZ

PART #	WATTAGE & LUMEN & EFFICACY	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WPSL				
	18 : 18W 2000LM 110lm/W	7 : 70 30: 3000K	UV : 120~277V Universal Voltage	BZ: Bronze
	26 : 26W 2860LM 110lm/W	8 : 80 40: 4000K 50: 5000K	10V: 0-10V Dimming PH: Photocell	



FEATURES:

- Robust die-cast aluminum housing, elegant slim design Mini Slim Wall Pack
- High Transmission Glass Diffuser, white or frosted optional
- Low-watt consumption with high-efficient LEDs
- 120V Line Voltage, Driver-On-Board Solution
- IP65 Suitable for wet location
- 50,000H @L70 long lifetime



ORDERING GUIDE Example: WPSM-15-830-UV10V-BZ

PART #	WATTAGE & LUMEN & EFFICACY	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WPSM				
	15 : 15W 2000LM >130lm/W	8 : 80 30: 3000K	UV : 120~277V Universal Voltage	BZ: Bronze
	20 : 20W 2600LM >130lm/W	40: 4000K	10V: 0-10V Dimming P: 0-10V Dimming	BK: Black
	30 : 30W 3900LM >130lm/W	50: 5000K	EM: Emergency Battery	