

PMC6

Cylinder Pendant Light Fixture



FEATURES:

- Cylinder Pendant Light Fixture, Robust Aluminum Housing
- Diameter 6", Height 9.8"
- E26 Socket, Par 30 Lamp (included)
- Canopy: D5" H: 1" Round
- 120V Line Voltage,
- Triac Dimming, 10-100% Dim Range
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: PMC6-609-927-UV-BK

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
PMC6				
	6: OD 6" x H 9.8" 09: 9W Par30 Lamp	9: 90 27: 2700K 30: 3000K 40: 4000K	UV: 120V ~ 277V Universal Voltage TR: Triac Dimming	BK: Black

PMC8

Pendant Round Cap Light Fixture



FEATURES:

- Round Cap Pendant Light Fixture, Robust Aluminum Housing
- Diameter 6", Height 9.8"
- E26 Socket, Par 30 Lamp (included)
- Canopy: D5" H: 1" Round
- 120V Line Voltage,
- Triac Dimming, 10-100% Dim Range
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: PMC8-1809-927-UV-BK

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
PMC8				
	18: OD 18" x H15" 09: 9W A19 Bulb	9: 90 27: 2700K 30: 3000K 40: 4000K	LB: 120V Line Voltage TR: Triac Dimming	WH: White


PMRF

Round Fabric Double Layer Pendant Fixture



FEATURES:

- Decorative Fabric Double Layer LED Pendant Light Fixture
- White Fabric Shade and Brushed Metal Ring
- Diameter 22.3" x Height: 6"
- 3 x E26 socket, A19 Bulbs (not included)
- Canopy: D5" H: 1" Round
- 120V Line Voltage, 3 x E26 Socket
- Triac Dimming, 10-100% Dim Range
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: PMRF-2227-927-LV-WH

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
PMRF				
	22: OD 22.3" 27: 3 x 9W A19	9: 90 27: 2700K 30: 3000K	LV: 120V Line Voltage TR: Triac Dimming	BN: Brushed Nickel WH: White

PMDM

Dome Pendant Light Fixture



FEATURES:

- Decorative LED Dome Sphere Pendant Light Fixture, Anodized Aluminum
- Diameter 22.3" x Height: 6"
- 3 x G9 Base, 5W Lamps (included)
- Canopy: D5" H: 1" Round
- 120V Line Voltage,
- Triac Dimming, 10-100% Dim Range
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: PMDM-1815-927-LV-WH

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
PMDM				
	18: D 13.8" x H 6" 15: 3 x 5W G9 Lamp	9: 90 27: 2700K 30: 3000K	LB: 120V Line Voltage TR: Triac Dimming	AL: Anodized Aluminum