

WSV1

Wall Mount Sconce Vertical Fixture



FEATURES:

- Vertical Sconce Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission plastic diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: WSV1-709-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WSV1				
	7: 7x10" 09: 9W	8: 80 27: 2700K	LB: 120V Line Voltage	BN: Brushed Nickel
	12: 12W	30: 3000K	TR: Triac Dimming	ORB: Oil Rubbed Bronze
	15: 15W	40: 4000K	Driver-On Board	BK: Black
		50: 5000K		
		3C: 3000/4000/5000K Selectable		


WSV2

Wall Mount Sconce Vertical Fixture



FEATURES:

- Vertical Sconce Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission plastic diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: WSV2-712-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WSV2				
	7: 7-1/2x12-1/4" 12: 12W	8: 80 27: 2700K	LB: 120V Line Voltage	BN: Brushed Nickel
	15: 15W	30: 3000K	TR: Triac Dimming	ORB: Oil Rubbed Bronze
		40: 4000K	Driver-On Board	BK: Black
		50: 5000K		
	17: 17W	3C: 3000/4000/5000K Selectable	UV: 120 ~ 277V Universal Voltage	
			TR: Triac Dimming at 120V only	



UILED Technology Ltd.
www.uiled.cn

C2314 Innovation Plaza, Pingshan Avenue, Shenzhen, 518118 China
Tel: (86) 8999 4991 Email: info@uiled.cn / sales@uiled.cn

WSB1

Wall Mount Sconce Brick Clean



FEATURES:

- Clean Brick Sconce Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission glass diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: WSB1-806-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WSB1				
	8: 8x8" 06: 6W	8: 80 27: 2700K	LB: 120V Line Voltage	BN: Brushed Nickel
	09: 09W	9: 90 30: 3000K	TR: Triac Dimming	
	12: 12W	40: 4000K	Driver-On Board	
		50: 5000K		ORB: Oil Rubbed Bronze


WSC1

Wall Mount Sconce Cup Fancy



FEATURES:

- Fancy Cup Sconce Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission glass diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: WSC1-806-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WSC1				
	8: 8x8" 06: 6W	8: 80 27: 2700K	LB: 120V Line Voltage	BN: Brushed Nickel
	09: 09W	9: 90 30: 3000K	TR: Triac Dimming	
	12: 12W	40: 4000K	Driver-On Board	
		50: 5000K		ORB: Oil Rubbed Bronze
		3C: 3000/4000/5000K Selectable		



UiLED Technology Ltd.
www.uiled.cn

C2314 Innovation Plaza, Pingshan Avenue, Shenzhen, 518118 China
Tel: (86) 8999 4991 Email: info@uiled.cn / sales@uiled.cn

WSS1

Wall Mount Sconce Semicircle Fixture



FEATURES:

- Semicircle Sconce Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission glass diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: WSS1-1512-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WSS1				
	15: 15x 7-1/2" 12: 12W	8 : 80 27: 2700K	LB : 120V Line Voltage TR: Triac Dimming	BN: Brushed Nickel
	15: 15W	9 : 90 30: 3000K	Driver-On Board	ORB: Oil Rubbed Bronze
	17: 17W	40: 4000K		
		50: 5000K		
		3C : 3000/4000/5000K Selectable		


WSS2

Wall Mount Sconce Semicircle Fixture



FEATURES:

- Semicircle Sconce Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission glass diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: WSS2-1612-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT (K)	INPUT (V) & CONTROL	FINISH
WSS2				
	16: 16-1/2 x 8" 12: 12W	8 : 80 27: 2700K	LB : 120V Line Voltage TR: Triac Dimming	BN: Brushed Nickel
	15: 15W	9 : 90 30: 3000K	Driver-On Board	ORB: Oil Rubbed Bronze
	17: 17W	40: 4000K		
		50: 5000K		
		3C : 3000/4000/5000K Selectable		



UiLED Technology Ltd.
www.uiled.cn

C2314 Innovation Plaza, Pingshan Avenue, Shenzhen, 518118 China
Tel: (86) 8999 4991 Email: info@uiled.cn / sales@uiled.cn

VAC1

Bath Vanity Classic Wall Mount Fixture



FEATURES:

- Classic Bath Vanity Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission plastic diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: VAC1-225-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT SELECTABLE (K)	INPUT (V) & CONTROL	FINISH
VAC1				
	2 : L 2' 25 : 25W	8 : 80 30 : 3000K	LB : 120V Line Voltage Driver-On Board	BN: Brushed Nickel
	3 : L 3' 30 : 30W	9 : 90 40 : 4000K	UV : 120 ~ 277V Universal Voltage	ORB: Oil Rubbed Bronze
	4 : L 4' 40 : 40W	3C : 3000/4000/5000K Selectable	UVD : 120~277V Universal Voltage	
			TR: Triac Dimming	
			N : Non Dimming	
			10V: 0-10V Dimming	



VAS2

Bath Vanity Classic Wall Mount Fixture



FEATURES:

- Classic Bath Vanity Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission plastic diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: VAS2-225-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT SELECTABLE (K)	INPUT (V) & CONTROL	FINISH
VAS2				
	2 : L 2' 25 : 25W	8 : 80 30 : 3000K	LB : 120V Line Voltage Driver-On Board	BN: Brushed Nickel
	3 : L 3' 30 : 30W	9 : 90 40 : 4000K	UV : 120 ~ 277V Universal Voltage	ORB: Oil Rubbed Bronze
	4 : L 4' 40 : 40W	3C : 3000/4000/5000K Selectable	UVD : 120~277V Universal Voltage	
			TR: Triac Dimming	
			N : Non Dimming	
			10V: 0-10V Dimming	



UiLED Technology Ltd.
www.uiled.cn

C2314 Innovation Plaza, Pingshan Avenue, Shenzhen, 518118 China
Tel: (86) 8999 4991 Email: info@uiled.cn / sales@uiled.cn

VAD3

Bath Vanity Fixture Design Series



FEATURES:

- Design Bath Vanity Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission plastic diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: VAD3-225-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT SELECTABLE (K)	INPUT (V) & CONTROL	FINISH
VAD3				
	2 : L 2' 25 : 25W	8 : 80 30 : 3000K	LB : 120V Line Voltage Driver-On Board	BN : Brushed Nickel
	3 : L 3' 30 : 30W	9 : 90 40 : 4000K	UV : 120 ~ 277V Universal Voltage	ORB : Oil Rubbed Bronze
	4 : L 4' 40 : 40W	3C : 3000/4000/5000K Selectable	UVD : 120~277V Universal Voltage	
			TR : Triac Dimming	
			N : Non Dimming	
			10V : 0-10V Dimming	

VAD4

Bath Vanity Fixture Design Series



FEATURES:

- Design Bath Vanity Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission plastic diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: VAD4-225-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT SELECTABLE (K)	INPUT (V) & CONTROL	FINISH
VAD4				
	2 : L 2' 25 : 25W	8 : 80 30 : 3000K	LB : 120V Line Voltage Driver-On Board	BN : Brushed Nickel
	3 : L 3' 30 : 30W	9 : 90 40 : 4000K	UV : 120 ~ 277V Universal Voltage	ORB : Oil Rubbed Bronze
	4 : L 4' 40 : 40W	3C : 3000/4000/5000K Selectable	UVD : 120~277V Universal Voltage	
			TR : Triac Dimming	
			N : Non Dimming	
			10V : 0-10V Dimming	



UiLED Technology Ltd.
www.uiled.cn

C2314 Innovation Plaza, Pingshan Avenue, Shenzhen, 518118 China
Tel: (86) 8999 4991 Email: info@uiled.cn / sales@uiled.cn


VAD1

Bath Vanity Fixture Design Series



FEATURES:

- Design Bath Vanity Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission plastic diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: VAD1-225-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT SELECTABLE (K)	INPUT (V) & CONTROL	FINISH
VAD1				
	2 : L 2' 25 : 25W	8 : 80 30 : 3000K	LB : 120V Line Voltage Driver-On Board	BN: Brushed Nickel
	3 : L 3' 30 : 30W	9 : 90 40 : 4000K	TR: Triac Dimming	
	4 : L 4' 40 : 40W	50 : 5000K	UV : 120 ~ 277V Universal Voltage	ORB: Oil Rubbed Bronze
		3C : 3000/4000/5000K Selectable	N : Non Dimming	
			10V: 0-10V Dimming	

VAD2

Bath Vanity Fixture Design Series



FEATURES:

- Design Bath Vanity Wall Mount Fixture
- Die-formed cold-rolled steel housing with high transmission plastic diffuser
- High efficiency 2835 LED module
- Triac Dimming, 1-100% dim range
- High Power Factory, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime



ORDERING GUIDE Example: VAD2-225-827-LBTR-BN

PART #	SIZE & WATTAGE (W)	CRI & CCT SELECTABLE (K)	INPUT (V) & CONTROL	FINISH
VAD2				
	2 : L 2' 25 : 25W	8 : 80 30 : 3000K	LB : 120V Line Voltage Driver-On Board	BN: Brushed Nickel
	3 : L 3' 30 : 30W	9 : 90 40 : 4000K	TR: Triac Dimming	
	4 : L 4' 40 : 40W	50 : 5000K	UV : 120 ~ 277V Universal Voltage	ORB: Oil Rubbed Bronze
		3C : 3000/4000/5000K Selectable	N : Non Dimming	
			10V: 0-10V Dimming	



UiLED Technology Ltd.
www.uiled.cn

C2314 Innovation Plaza, Pingshan Avenue, Shenzhen, 518118 China
Tel: (86) 8999 4991 Email: info@uiled.cn / sales@uiled.cn