



- Robust die-cast aluminum housing
- Elegant yet rugged construction effortlessly integrates with existing architecture.
- 120-277V wide range input voltage
- 0-10V dimming standard
- Complies with UL1598 and CSA C22.2
- DLC Premium Listed
- IP65 Rated Enclosure, Suitable for Wet Locations
- 100,000H @ L70 long lifetime



ORDERING GUIDE

PART #	INPUT (Vac)	OUTPUT (W)	LUMEN OUTPUT (LM)	EFFICACY (LPW)	CRI	AVAILABLE CCT (K)	DIMMING	FINISH	CERTIFICATION
WPSL-18	120-277	18	1880-2000	110	>80	3000/4000/5000	0-10V	BRONZE	ETL, DLC P
WPSL-26	120-277	26	2720-2860	110	>80	3000/4000/5000	0-10V	BRONZE	ETL, DLC P


KEY FEATURES

- Housing is protected by a RoHS compliant, corrosion resistant powder coat finish.
- Beam Angle 120 °
- System power factor > 0.9 and THD <20%.
- Operating temperature: -25°C to 40°C (-13°F to 104°F).
- Luminaire is ready to be surface mounted.
- Net Weight: 1.2KG (2.64 lbs).

- **Optional Accessories:** Photocell





LUMINAIRE PHOTOMETRIC



IESNA	LM-63-2002
Light source	LED
Input Watts	26
Total Lumens	2860
Efficiency	110 LPW
Beam Angle	121.8 DEG

DIMENSION

Size (mm)	18W	26W
A	205	281
B	165	216
C	98	110



PACKAGING

PART#	UNIT / BOX	MASTER BOX	WEIGHT	UNITS/40'HQ FCL	VOLUMN	WEIGHT
WPSL-18	6	560 x 270 x 260 mm	9.5 KG	9,600	62 CBM	15000 KG
WPSL-26	6	560 x 270 x 260 mm	9.5KG	9,600	62 CBM	15000 KG